

FFC SNOW BLOWER LOW-FLOW



FFC Low Flow Snow Blowers are known as the work horse of the industry. They are designed with the operator in mind and provide all of the features you would expect from a commercial piece of equipment.

FFC Low Flow Snow Blower Features:

- Two stage hydraulic blower throws snow up to 45ft.
- Electronic or electro/hydraulic poly-lined chute and deflector.
- Reinforced wrapper makes it one of the toughest Snow Blowers in the industry.
- High-volume 25" shroud opening
- Provides excellent visibility
- Replaceable wear-resistant Pacal steel tapered wear edge
- Skid shoes are adjustable and replaceable.
- Attaches quickly to most skid-steer loader brands

IMPORTANT: All replacement hydraulic hoses and fittings must have a minimum rated working pressure of 4000 psi. Hoses and hydraulic couplers from the attachment to the loader are included for skid-steers only.

Model	LAF6748A	11005C	11005D	11005E	11006D	11006E	11008D	11008E	11007D	11007E
Weight	490 lbs.	650 lbs.	650 lbs.	650 lbs.	685 lbs.	685 lbs.	703 lbs.	703 lbs.	720 lbs.	720 lbs.
Cutting Width	48"	60"	60"	60"	72"	72"	78"	78"	84"	84"
Cutting Height	25"	25"	25"	25"	25"	25"	25"	25"	25"	25"
Depth	38"	38"	38"	38"	38"	38"	38"	38"	38"	38"
Height	57"	57"	57"	57"	57"	57"	57"	57"	57"	57"
Auger Motors	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single
Auger Diameter	14"	14"	14"	14"	14"	14"	14"	14"	14"	14"
Fan Diameter	18"	18"	18"	18"	18"	18"	18"	18"	18"	18"
PSI Range	1800-2500	2000-3000	2000-3000	2000-3000	2000-3000	2000-3000	2000-3000	2000-3000	2000-3000	2000-3000
GPM Range	8-13	12-25	14-21	18-27	14-21	18-27	14-21	18-27	14-21	18-27
Hose ID	1/2"	1/2"	1/2"	5/8"	1/2"	5/8"	1/2"	5/8"	1/2"	5/8"



SKID STEER
SOLUTIONS.COM

Your Online Source for Skid Steer Attachments!

Phone: 866.966.2538/360.966.2538

Fax: 360.966.7118

Email: sales@skidsteersolutions.com